

# PATENT SPECIFICATION

(11) 1 605 421

1 605 421

(21) Application No. 6705/70  
(31) Provisional Application No. 6705/70  
(44) Complete Specification published 18 November 1998  
(51) Int. Cl<sup>6</sup> C06B 25/24  
(52) Index at acceptance  
C1D D6A1B D6A1D D6A1G D6A2D D6A2E D6A2F  
D6B4

(22) Filed 10 May 1971  
(32) Filed 11 February 1970  
(19)



(72) Inventors Colin George Lawson Gordon Anthony Palmer

## (54) IMPROVEMENTS IN OR RELATING TO STABILISERS FOR PROPELLANTS

I, Secretary of State for Defence, London, do hereby declare the invention for which I pray that a patent may be granted to me, and the method by which it is to be performed, to be particularly described in and by the following statement:-

This invention relates to novel stabilisers for use in composite-modified double-base propellants and to propellants containing them.

It is known that double-base propellants, that is propellants containing nitrocellulose and a liquid nitrate ester or a mixture of liquid nitrate esters, require a small proportion of stabiliser in order to permit long-term storage. In the absence of the stabiliser, the propellant compositions slowly become acidic due to decomposition of the nitrate esters. This acidity catalyses further decomposition resulting in a degradation of mechanical and ballistic properties and even a dangerous degree of self-heating which may lead to a disastrous ignition.

A small amount of chalk or similar mild alkali is used in the nitro-cellulose during its stabilisation prior to mixing with the other propellant ingredients and is included, therefore, amongst conventional stabilisers. In addition, an organic substance or mixture of substances, including substituted ureas such as diethyl diphenyl urea (carbamite), urethanes such as methyl phenyl urethane, or nitrodiphenylamine (NDPA) are used in proportions up to about 3%. Diphenylamine may be used at low nitroglycerine contents (up to about 15 per cent nitroglycerine). Higher proportions of stabilisers may be used to improve plasticisation or to moderate ballistic properties but these higher proportions are not normally required for stabilisation as such.

Other ingredients, such as a fuel and/or a source of oxygen, for instance a metal powder and/or ammonium perchlorate, may be added to double-base propellants to modify specific properties such as energy release. These propellants are known as composite-modified double-base propellants (CMDB). The stability of these propellants when modified to include ammonium perchlorate is, however, unacceptable even when the heretofore mentioned stabilisers are used. As used in this specification the expression

composite-modified double-base propellant (CMDB) refers to those propellants which include ammonium perchlorate as an essential ingredient.

The life of a propellant may be assessed by different criteria as, for instance, its chemical stability which may be a main factor in its safety characteristics or its physical stability which in general determines the continuance of its ballistic properties. The effective life is, of necessity, determined by the shortest time given by any of these criteria. In the case of composite-modified double-base propellants, the principal reasons for unacceptable stability have been (1) the poor stability as shown by the flammability and cracking tests and (2) a low total stabilising capacity as shown by the flammability test.

Acceptable stability of CMDB propellants is not automatically attained by a simple increase in the proportion of the conventional stabiliser present. These stabilisers act by combining with the oxides of nitrogen produced by the decomposition of the nitrate esters and do not of necessity react with the breakdown products of ammonium perchlorate and other oxidising agents. There is, in addition, a limited solubility of these stabilisers in the propellant matrix as evidenced by 'blooming' on storage. Also an excess of stabiliser detracts from the energy of the propellant.

It has now been found that composite-modified double-base propellants may be successfully stabilised to permit long-term storage by using a stabiliser comprising a mixture of any known stabiliser for double-base propellants and at least two of the compounds nitroguanidine, para-nitro-N-methyl aniline, and an inorganic compound as hereinafter defined.

The inorganic compound for use in the invention is defined as a basic compound which reacts with strong acids but is not sufficiently basic to react directly with the other ingredients, particularly ammonium perchlorate or the nitrate esters, to any significant extent. It will not react with the other ingredients to form sensitive metallic salts nor act as a decomposition catalyst for the nitrate esters.

According to the invention, there is provided a stabiliser for use in composite-modified

BEST AVAILABLE COPY

double-base propellants comprising a mixture of at least three compounds of any known stabiliser for propellants and at least two of the compounds nitroguanidine, para-nitro-N-methyl aniline, and an inorganic compound as hereinbefore defined.

5 Preferably, the stabiliser mixture contains all three of the compounds nitroguanidine, para-nitro-N-methyl aniline and an inorganic compound in addition to the known stabiliser or stabilisers.

10 The use of nitroguanidine has the advantage that it is self-energetic and as a consequence much larger quantities of it may be used than is normal for conventional stabilisers.

15 Preferably, the inorganic compound is lead carbonate or a basic lead carbonate.

Stabilisers known to the art may include diphenylamine, 2-nitrodiphenylamine, diethyl diphenyl urea, p-nitro-N-methyl aniline and methyl phenyl urethane.

20 The invention also provides novel composite-modified double-base propellants containing the mixture of stabilisers as hereinbefore described.

25 The novel propellants contain nitro-cellulose within the range 14% to 35%, at least one nitrate ester, such as nitro-glycerine, diethylene glycol dinitrate, triethylene glycol dinitrate or trimethylol ethane trinitrate within the range 30 25% to 40%, a non-explosive desensitiser such as an ester, for example dimethyl phthalates or triacetin, within the range up to 8%, an oxidising agent consisting at least in part of ammonium perchlorate within the range 5% to 50%, a fuel 35 such as aluminium powder within the range up to 25% and a mixture of stabilisers within the range 2.5% to 10%. All percentages are by weight.

40 Preferably the non-explosive desensitiser is a phthalate ester. It has been found that triacetin in the presence of ammonium perchlorate whilst giving compositions having an acceptable stability, tends to enhance the development of acidity on storage.

45 The effectiveness of stabilisers in propellants is usually confirmed by storage trials at elevated temperatures whereby the rate of decomposition is accelerated and the effective life of the propellant at ambient temperatures may be 50 determined relatively quickly. The life of the propellant may be affected by a reduction in the amount of stabiliser due to nitration or nitrosation of the stabiliser by oxides of nitrogen produced by decomposition of the nitrate esters 55 or more usually by a physical deterioration (cracking) due to the evolution of small amounts of gases including permanent gases as for instance nitrogen. Conventional known stabilisers allow the propellant to generate gases 60 on hot storage including the permanent gases which are not very soluble in the propellant, and which diffuse away very slowly. When the thickness of the propellant is large and/or its

temperature is too high, the gas evolved may cause fissures in the propellant creating extra burning surfaces and affecting the internal ballistics.

65 A series of CMDB propellants were prepared to the following composition: nitrocellulose (12.6%N) 22.0%; nitroglycerines 28.9%; ammonium perchlorate, 24.7%; aluminium, 16.4%; and triacetin, 7.0%. All percentages are by weight.

70 To these, varying proportions of the novel stabiliser system, nitroguanidine (picrite), a basic lead carbonate (WL), and para-nitro N-methylaniline (NMA) were added in addition to a known stabiliser, 2-nitro diphenylamine (NDPA) and the prepared propellants were subjected to hot storage trials, using as controls 75 propellants made to the above composition containing 1.0 per cent of NDPA and others containing about 4 per cent of mixtures of NPA and NMA. In one of the novel prepared propellants (Sample 4) the triacetin was replaced 80 by dimethyl phthalate and in another, (Sample 6), the nitroglycerine and triacetin were replaced by diethylene glycol dinitrate.

85 The initial stabiliser content of the propellants and the effect of storage at varying temperatures is given in Table 1.

90 Tests carried out include an X-ray examination for the appearance of cracks followed by a destructive visual examination, and a flammability test in which cubes of the propellant, wrapped in aluminium foil, were 95 stored in loosely plugged stainless-steel tubes heated to 95° C until ignition occurred, when the plugs were ejected.

100 The prepared propellants were also stored at 80° C and analyses were carried out at regular intervals to determine the percentage of residual NDPA and NMA. These results are given in Table 2. Similar results obtained from larger 105 charges stored at 60° C are given in Table 3. Owing to analytical difficulties, the percentages of WL and picrite are not given.

110 In all cases, the novel propellants according to the invention had much greater stability and freedom from physical defects than the control propellants.

Sample No 6 containing the combination of NDPA, NMA, basic lead carbonate and nitroguanidine with diethylene glycol dinitrate was outstanding and Sample No 4 containing 115 dimethyl phthalate as the plasticiser was excellent.

What we claim is:-

1. A stabiliser for use in composite-modified double-base propellants comprising a mixture of 120 at least three components including any known stabiliser for propellants and at least two of the compounds nitroguanidine, para-nitro-N-methyl aniline and an inorganic compound as hereinbefore defined.

125

BEST AVAILABLE COPY

2. A stabiliser according to Claim 1 comprising a mixture of any known stabiliser for propellants and nitroguanidines para-nitro-N-methyl aniline, and an inorganic compound as hereinbefore defined. 25
- 5 3. A stabiliser according to Claim 1 or Claim 2 wherein the inorganic compound is lead carbonate or a basic lead carbonate. 30
- 10 4. A stabiliser according to any one of Claims 1 to 3 wherein the known stabiliser is at least one of the compounds, diphenylamine, 2-nitro diphenylamine, diethyl diphenyl urea, p-nitro-N-methyl aniline, and methyl phenyl urethane. 35
- 15 5. A composite-modified double-base propellant incorporating at least in part a stabiliser according to any one of Claims 1 to 4 comprising nitrocellulose within the range 14 per cent to 35 per cent by weight, at least one 40
- 20 nitrate ester within the range 25 per cent to 40 per cent by weight, a non-explosive desensitiser within the range up to 8 per cent by weight, an oxidising agent consisting at least in part of ammonium perchlorate in the range 5 to 50 per cent by weight, a fuel within the range up to 25 per cent by weight and a mixture of stabilisers within the range 2.5 per cent to 10 per cent. 45
6. A composite-modified double-base propellant according to Claim 5 wherein the nitrate ester is nitro-glycerine, diethylene glycol dinitrate, triethylene glycol dinitrate or trimethylol ethane trinitrate.
7. A composite-modified double-base propellant according to Claim 5 or Claim 6 wherein the non-explosive desensitiser is an ester. 35
8. A composite-modified double-base propellant according to Claim 7 wherein the ester is dimethyl phthalate or triacetin.
9. A composite-modified double-base propellant according to any one of Claims 5 to 8 wherein the fuel is aluminium powder. 40
10. A composite-modified double-base propellant according to Claim 5 substantially as described in the specification. 45

Printed by Microgen Current Knowledge, Wokingham RG41 2QY, 1998

Typeset by Document Design, Wokingham, RG40 1BJ.

Published by The Patent Office, Concept House, Cardiff Road, Newport, Gwent NP9 1RH.

Further copies may be obtained from The Patent Office, (Sales)  
Concept House, Cardiff Road, Newport, South Wales NP9 1RH.

**BEST AVAILABLE COPY**

Table 1  
Effect on Thermal Stability and Cracking

Sample No.	Stabilizers (per cent)				12.7 mm Cubes Firing times at 950°C (hrs)	Cracking Life	
	NDPA	III A	WT	Ptc. Flow		50 mm. Cubes at 80°C (days)	150 mm. Cylinders at 60°C (weeks)
1	0.3	1.1	0.35	2.15	24.5	13	44
2	1.0	0.35	11.1	2.10	154, 190	6	26
3	1.0	1.1	0.35	11.1	117, 135	16	21*
4	1.0	0.35	0.35	2.15	216	20	59
5	1.0	0.35	0.35	2.10	≥ 216	13	43
6	1.0	0.35	0.35	2.20	> 216	31	> 52
7	0.7	-	-	-	-	1	-
8	1.0	-	-	-	30	1 - 3	-
9	1.0	-	-	-	48	1 - 2	-
10	1.0	-	-	-	38	1 - 2 (50 mm cylinder)	-
11	3.0	0.8	-	-	89, 76	0 - 1	14 - 21
12	0.85	3.0	-	-	88, 81	0 - 1	14 - 21

\*Plugs were discrete bubbles and not usual gas cracking flaws

BEST AVAILABLE COPY

Table 2  
 Percentages Residual Stability at 80°C on 50 ml. Cubes

Storage time (weeks)	Sample 7	Sample 8	Sample 9	Sample 11		Sample 12		Sample 1	Sample 2		Sample 3		Sample 4		Sample 5	Sample 6	
	NDPA	NDPA	NDPA	NDPA	NDPA	NDPA	NDPA	NDPA	NDPA	NDPA	NDPA	NDPA	NDPA	NDPA	NDPA	NDPA	NDPA
0	0.7	1.0 0.51 (8 days)	1.0 0.56 (8 days)	0.8 0.35 (3 days)	3.0 1.84 (3 days)	3.0 1.84 (3 days)	0.85 0.65 (3 days)	1.0 0.75	0.29 0.25	0.35 0.05	1.0 0.94	1.0 0.75	0.53 0.97	0.35 1.0	0.35 1.0	0.35 1.0	1.0
1	0.37	-	-	-	-	-	-	0.52	0.25	0.05	0.14	0.52	0.92	-	0.05	0.69	-
2	-	-	-	-	-	-	-	0.105	0.19	0.05	0.24	0.12	0.73	-	-	-	-
3	-	-	-	-	-	-	-	0.09	0.11	0.05	0.05	-	-	-	-	-	-
4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
6	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
7	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

BEST AVAILABLE COPY

Table 3  
Percentage Incipient Cracking at 60°C on 150 mm diameter Soda Glass

Storage Time (weeks)	Sample 11		Sample 12		Sample 1		Sample 2		Sample 3		Sample 4		Sample 5		Sample 6	
	HDPA	HVA	HDPA	HVA	HDPA	HVA	HDPA	HVA	HDPA	HVA	HDPA	HVA	HDPA	HVA	HDPA	HVA
0	3.0 1.67 (21 days)	0.8 0.77 (21 days)	0.85 0.52 (21 days)	3.0 1.62 (21 days)	0.30 0.31	1.1 0.77	1.0 0.91	0.35 0.10	0.98 0.94	1.0 0.73	1.0 0.35	1.0 0.35	1.0 0.35	1.0 0.35	1.0 0.35	0.35
13	-	-	-	-	-	-	-	-	0.91 Cracked in 21 weeks not typical flaws	0.62	-	-	-	-	-	-
23	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
26	-	-	-	-	0.25	0.57	0.85 Cracked in 26 weeks 0.05 (27 weeks)	-	-	-	-	-	-	-	-	-
39	-	-	-	-	0.24	0.44	-	-	-	-	-	-	-	-	-	-
40	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
45	-	-	-	-	Cracked in 44 weeks 0.24, 0.34	-	-	-	-	-	-	-	Cracked in 43 weeks 0.87, 0.05	-	-	-
48	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
52	-	-	-	-	0.24	0.25	0.54 0.05	0.78	0.32	-	-	-	-	-	0.80 not cracked in 52 weeks	0.05
60	-	-	-	-	-	-	-	-	-	-	Cracked in 59 weeks 0.79, 0.05	-	-	-	-	-

BEST AVAILABLE COPY